



BLM.ID2-N2/C4 Motorcyclist protection system

PERFORMANCE PARAMETERS

Continuous motorcyclist protection system, which is installed on a safety barrier with posts CPN 120 every 4,00 m, formed by a lower motorcyclist protection part of double wave and a connector.

FEATURES

Post connectors and span connectors are the same.

ADVANTAGES

Easy assembling.
It doesn't require any component to be disassembled.
Its low weight and simplicity make it easy to transport, handle, assemble and maintain.

MATERIALS

Steels as per EN 10025.

DURABILITY

Hot Dip Galvanization as per EN ISO 1461.

	EN 1317	EN 135900
Containment Level	N2	60 Km/H
Severity Index	A	Level I
Working Width	W5	
Dynamic deflection	1,2	

CRASH TESTS (AS PER EN 1317)



Test: TB32
(car 1500 Kg, 110 Km/h, 20°)
Code: E10-2416
Date: 16/07/2010
Laboratory: CIDAUT

E10-2416 136



Test: TB11
(car 900 Kg., 100 Km/h, 20°)
Code: E10-2776
Date: 03/09/2010
Laboratory: CIDAUT

E10-2776 180

CRASH TESTS (AS PER EN 135900)



Test: TM.1.60
(Mannequin strikes a post, 60 Km/h, 30°)
Code: E10-1818
Date: 02/06/2010
Laboratory: CIDAUT

E10-1818 135



Test: TM.3.60
(Mannequin strikes the half of a span, 60 Km/h, 30°)
Code: E10-1817
Date: 02/06/2010
Laboratory: CIDAUT

E10-1817 180